

MF21 40

New model: Large square baler



- New model to complete the line up of five key bale sizes
- Bale size 0.8 m wide x 0.7 m tall
- Length up to 2.7 m
- Pick-up 2.26 m working width
- Choice of single or tandem axles
- Choice of standard packer or rotor cutter configuration
- ISOBUS 11783 Compatible implement



VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT



MASSEY FERGUSON

Specifications

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

● = Standard
○ = Optional

Bale size			MF 2140
Cross section (width x height)	mm		800x700
Length (maximum)	mm		Up to 2740
Dimensions and Weights			
Overall width - single / tandem axle	mm		2550 / 2590
Overall length - bale chute folded for transport	mm		8300
Overall height – to top of hand rail	mm		3270
Weight (single axle / tandem axle, less cutter)	kg		6090 / 7170
Weight (single axle / tandem axle, with cutter)	kg		6920 / 8000
Main Drive			
Protection			Slip and overrun clutches, shearbolt
Gearbox type			Enclosed, double reduction
Plunger			
Speed	strokes/min		47
Length of stroke	mm		740
Pickup			
Effective working width	mm		2260
Protection			Slip and overrun clutches
Suspension			Torsion bar system
Feeding System			
Packers			Fork type, 4 hardened tines
Protection			Splined slip clutch
Tying Mechanism			
Number / type of knotters			4 Double knot
Twine type / capacity			High quality polypropolene / 30 ball storage
Knotter Blower			Standard - hydraulically driven
Differential			Mechanical
Tyres			
Single axle			600 / 50 - 22.5
Tandem axle			500 / 50 - 17
Lights			
			CE compliant road lighting, with three work lights & three service lights
Control and Monitoring System			
			ISOBUS 11783 Compatible, GTA 1 full colour console
Tractor Requirements			
Recommended PTO horsepower - Packer	hp / kW		140 / 105
Recommended PTO horsepower - Cutter	hp / kW		170 / 127
PTO operating speed	rev/min		1000
PTO type			Type II 1 3/8" (35 mm) - 21 Spline CV PTO Shaft
Hydraulics spool valve requirements			2 or 3 double acting auxiliary valves
Standard Equipment			Two rail bale ejector, knotter blower, autolube, heavy duty roller bale chute
Optional Equipment			Cutter unit, Tandem axle, Air brakes Type III 1 3/4" (44 mm) 20 Spline CV PTO Shaft Integrated Bale Weighing System - available 2011 season